

The optimum choice for training, maintenance and prototyping

The new CNC lathes of the SMS series are robust and accurate machines equipped with a geared headstock providing high torque for the most demanding roughing work.

The new JAP beds provide increased stiffness improving the dimensional and thermal stability of the machine and reduce the level of vibration during the turning process.

The SMS series are intuitive and user-friendly thanks to the conversational programming options offered with the controls Siemens or Fagor, ideal for the production of short series, prototyping and training centers.



STANDARD EQUIPMENT

- Siemens 808D Control
- Linear and solid Path Graphs
- Electronic handwheel for X and Z axes
- Increased width and stiffness of the bed
- Headstock with electronic speed variator 2 ranges
- Lubrication pump for the main spindle bearings
- High precision main spindle bearings
- Reducing bush of main shaft and dead center
- Dead center for tailstock
- Manual quick-change toolpost
- Automatic guide lubrication system
- Coolant equipment
- Complete guarding enclosure
- Cast iron pedestals
- Precision levelers
- LED Work light
- Instruction manual
- Verification standard DIN 8605
- CE Standard

OPTIONAL EXTRAS

- Control Fagor 8055i, Fagor 8058
- Chucks with 3 and 4 jaws
- Rear chuck
- Hydraulic power chuck
- Hydraulic collect chuck
- Hydraulic tailstock
- Fixed Steady Rest
- Large capacity fixed steady rest
- Follow Rest
- Multifix quick-change toolpost
- 4 and 8 position automatic turret
- Live center
- Chip conveyor
- Electric transformer
- Higher pressure cooling system
- Electric panel refrigeration
- Anti-vibration kit
- Remote jog unit
- Tool Presetter

> SMS

Technical data sheet

		SMS-200		SMS-250				SMS-325		
Working capacity										
Distance between centres	mm / in	1000/40	1500/60	1000/40	1500/60	2000/80	3000/120	1000/40	2000/80	3000/120
Bed width	mm / in	300 / 11 ^{3/4}		350 / 13 ^{3/4}				425 / 16 ^{3/4}		
Centre height	mm / in	200 / 7 ^{3/4}		250 / 9 ^{3/4}				325 / 13		
Ø max. swing over bed	mm / in	400 / 15 ^{3/4}		500 / 19 ^{1/2}				700 / 27 ^{1/2}		
Ø max. swing over carriage	mm / in	360 / 14		450 / 17 ^{1/2}				600 / 23 ^{1/2}		
Ø max. over cross slide	mm / in	200 / 7 ^{3/4}		290 / 11 ^{1/4}				400 / 15 ^{3/4}		
Cross slide travel	mm / in	235 / 9		310 / 12				400 / 15 ^{3/4}		
Length inal carriage travel	mm / in	850	1350	850	1350	1850	2850	850	1850	2850
Headstock										
Main motor power	kW	4		5,5				7.5		
Headstock main spindle bore <i>Valid for all centre distances</i>	mm / in	42 / 1 ^{1/2}		58 / 2 ^{1/4}		105 / 4		80 / 3	105 / 4	155 / 6
Main spindle nose	ASA/CAM-LOCK	A2 - 5 / D1 - 5		A2 - 6 / D1 - 6		A2 - 8 / D1 - 8		A2 - 8 / D1 - 8		A2 -11 / - -
Main spindle nose taper	MT	4		6		5		5		
Speed ranges	Range I	r.p.m.	0 - 575	0 - 520	0 - 312	0 - 375	0 - 312	0 - 200		
	Range II	r.p.m.	575 -2350	520 - 2080	312 - 1250	375-1500	241-1250	200-800		
X-axis, Z-axis										
Working feeds Z	Siemens	m/min	0 - 7				0 - 5			
	Fagor	m/min	0 - 10				0 - 8.5			
Working feeds X	Siemens	m/min	0 - 8.5				0 - 4			
	Fagor	m/min	0 - 12				0 - 6			
Rapid traverse Z	Siemens	m/min	9				6.5			
	Fagor	m/min	12.5				10			
Rapid traverse X	Siemens	m/min	10				5			
	Fagor	m/min	15				7.5			
Z - Ball screw, Ø/pitch	mm	40 / 10				50 / 10				
X - Ball screw, Ø/pitch	mm	20 / 5				32 / 5				
Tailstock										
Tailstock barrel Ø	mm / in	68 / 2 ^{1/2}		95 / 3 ^{3/4}				106 / 4		
Tailstock barrel travel	mm / in	200 / 7 ^{3/4}		220 / 8 ^{1/2}				225 / 8 ^{3/4}		
Tailstock Morse taper	MT	4		5				6		
Turret										
Manual turret										
Tool shank	mm	25x25				32x32				
Ø Boring bar	mm	20				25				
Dimensions and Weight										
Length	mm	2800	3350	2810	3525	3850	4750	3290	4290	5290
Width	mm	1270		1370		1450		2170		
Height	mm	1890		1910		1875		2090		
Weight	kg	1670	1980	1850	2200	2600	3200	5460	5760	6560
Options										
Fixed steady rest Ø	mm	10 - 125		10 - 140				55 - 180		
Large capacity fixed steady rest Ø	mm	110 - 200		140 - 300				180 - 400		
Mobile Steady Rest Ø	mm	10 - 80		10 - 90				10 - 140		
Dimensions and Weight with packaging										
Length	mm	2900	3450	2910	3625	3950	4850	3390	4390	5390
Width	mm	1470		1570		1650		2370		
Height	mm	2080		2100		2065		2180		
Weight	kg	1970	2280	2250	2600	3000	3600	5860	6160	6960

Note: The data is merely informative and subject to change according to the needs of the company.



Partida de la Sierra s/n • 22310 Castejón del Puente • Huesca (Spain)
+34 974 401 650 • info@metosagroup.com • www.japcnc.com

JAP is a registered trademark of:
www.metosagroup.com

