

▶ ST

MODELS ST 180 > ST 225 > ST 285 > ST 310

High precision flatbed CNC lathes.

The ST is Pinacho's high reliability numerical control lathe, with great rigidity and working precision. Developed with components of the highest quality and manufactured under strict and demanding control standards. ST parallel lathes incorporate the most advanced technology developed from experience provided by more than 75 years of history.

Our CNC flatbed lathes are silent, easy to use machines, with a headstock composed of a servo-motor and direct transmission to the main axis, providing a high speed of rotation and an excellent quality surface finish on the component.

The Pinacho ST are lathes with up to 3 axes that provide an extraordinary versatility in the world of machine tools.



STANDARD EQUIPMENT

- Fanuc Oi-TF Control
- Dynamic graphics / trajectory
- Profile editor
- Electronic handwheel for X and Z axes
- Direct drive headstock with servomotor
- Reducing bush of main shaft and dead centers
- 8-position automatic turret with 4 toolholders
- Automatic lubrication of the guideways
- Refrigeration equipment
- Cast iron pedestals
- Precision levellers
- Work light
- Instruction manual
- Verification standard DIN 8605
- CE Standard

OPTIONAL EXTRAS

- Control Fagor 8055i, Siemens 828D, Fagor 8058 or Fagor 8060
- Chucks with 3 and 4 jaws
- C-axis*
- Rear chuck
- Hydraulic power chuck
- Hydraulic collect chuck
- Hydraulic tailstock
- Fixed steady rest
- Large capacity fixed steady rest
- Follow rest
- Livetool 12 positions
- Live center
- Chip conveyor
- Electric transformer
- Higher pressure cooling system
- Electric panel refrigeration
- Anti-vibration kit
- Remote jog unit
- Tool presetter
- Bar feeder

*Note: *Not available for ST180*



TECHNICAL DATA SHEET

Working capacity		ST-180		ST-225		ST-285				ST-310				
Center distance	mm/in	750/30	1000/40	1000/40	1500/60	1000/40	1500/60	2000/80	3000/120	1000/40	1500/60	2000/80	3000/120	
Bed width	mm/in	250 / 10		300 / 12		350 / 14				350 / 14				
Centre height	mm/in	180 / 7		225 / 9		285 / 11				310 / 12				
Ø max. swing over bed	mm/in	360 / 14		450 / 18		570 / 22 1/2				620 / 24				
Ø max. swing over carriage	mm/in	300 / 12		370 / 15		510 / 20				550 / 21 1/2				
Ø max. over cross slide	mm/in	190 / 7		260 / 10		360 / 14				410 / 16				
Cross slide travel	mm/in	185 / 7 1/4		235 / 9 1/4		260 / 10				310 / 12				
Longitudinal carriage travel	mm/in	600/23 1/2	840/33	930/36 1/2	1450/57	850/33	1450/53	1850/72 1/2	2850/112	850/33	1450/53	1850/72 1/2	2850/112	
Headstock														
Main motor power	Fagor	kW	7.5		15		17				17			
	Fanuc	kW	11		15		15				15			
	Siemens	kW	7		9		11				11			
Headstock main spindle bore Valid for all centre distances	mm/in	42 / 1 1/2		65 / 2 1/2		80 / 3				105 / 4		155 / 6		
Main spindle nose	ASA/CAM-LOCK	A2 - 5 / D1 - 5		A2 - 6 / D1 - 6		A2 - 8 / D1 - 8				A2 - 8 / D1 - 8		A2 - 11 / --		
Main spindle nose taper	MT	4		4		5				5		5		
Speed ranges	r.p.m.	0-4000		0-3000		0-2500				0-2500		0-1000		
X-axis, Z-axis														
Working feeds Z	Fagor	m/min	0 - 10		0 - 10		0 - 10				0 - 10			
	Fanuc	m/min	0 - 10		0 - 10		0 - 10				0 - 10			
	Siemens	m/min	0 - 7		0 - 7		0 - 7				0 - 7			
Working feeds X	Fagor	m/min	0 - 12		0 - 12		0 - 12				0 - 12			
	Fanuc	m/min	0 - 12		0 - 12		0 - 12				0 - 12			
	Siemens	m/min	0 - 12		0 - 12		0 - 12				0 - 12			
Rapid traverse Z	Fagor	m/min	12.5		12.5		12.5				12.5			
	Fanuc	m/min	12.5		12.5		12.5				12.5			
	Siemens	m/min	9		9		9				9			
Rapid traverse X	Fagor	m/min	15		15		15				15			
	Fanuc	m/min	15		15		15				15			
	Siemens	m/min	15		15		15				15			
Z - Ball screw, Ø/pitch	mm					40 / 10								
X - Ball screw, Ø/pitch	mm					20 / 5								
Tailstock														
Tailstock barrel Ø	mm/in	58 / 2 1/4		68 / 2 1/2		95 / 3 3/4				95 / 3 3/4				
Tailstock barrel travel	mm/in	180 / 7		200 / 7 3/4		220 / 8 1/2				220 / 8 1/2				
Tailstock Morse taper	MT	4		4		5				5				
Turret														
Stations of standard turret		8				8								
Tool shank	mm	20x20				25x25								
Ø Boring bar	mm	32				40								
Dimensions and Weight														
Length	mm	2250	2520	2810	3325	2800	3320	3940	4750	2810	3325	3940	4750	
Width	mm	1170		1270		1360		1450		1450		1660		
Height	mm	1820		1890		1890		2110		1930		2060		
Weight	kg	1580	2400	2230	2500	2250	2475	2970	3640	2300	2515	3010	3700	
Options														
Fixed steady rest Ø	mm	10 - 125		10 - 140		10 - 180				10 - 180				
Large capacity fixed steady rest Ø	mm	110 - 200		140 - 250		180 - 350				180 - 400				
Follow rest Ø	mm	10 - 80		10 - 90		10 - 130				10 - 130				
Dimensions and weight with packaging														
Length	mm	2450	2720	3010	3525	3010	3520	4140	4950	3010	3525	4140	4950	
Width	mm	1270		1370		1470		1550		1550		1800		
Height	mm	2020		2090		2130		2310		2130		2310		
Weight	kg	1685	2500	2530	2600	2650	2875	3370	3940	2700	2915	3410	4100	

Note: The data is merely informative and subject to change according to the needs of the company.